

Data Sheet

Electramo NV Industrieweg 14 B-2390 Malle Belgium +32 3 311 65 40 info@electramo.com www.electramo.com BE 0414.941.452	Electric motor Type	YE3-180L-6 - 15kW - 975 rpm - 400V/690V					
	Efficiencies	IEC60034-30		IE3 (Premium Efficiency)			
	Insulation class	F / B					
	Temperatures	-20°C / +40°C					
	Connection - Phases	Δ	Y	Δ	Δ	Δ	
	Tension	V	400	690	440	460	480
	Frequency	Hz	50	50	60	60	60
	Output	kW	15,00	15,00	18,00	18,00	18,00
	Speed	min⁻¹	975	975	1170	1170	1170
	Current	A	29,30	16,99	31,97	30,58	29,30
	Efficiency	%	100% 91,20	75% 91,40	50% 90,80		
	Cos φ		100% 0,81				
	Starting Current	A	7,30	Ia/In			
	Nominal Torque	Nm	146,92	Nm			
	Starting Torque	Nm	2,00	Ms/Mn			
	Maximum Torque	Nm	2,10	Mmax/Mn			
	Construction		Cast Iron				
	Mounting position		B3 - IM1001 - feet - horizontal				
	Protection		IP 55				
	Cooling method		IC 411				
	Duty type		S1				
	Tropical treatment		95%				
	Max. altitude A.S.L.		1000 m				
	Paint (body / fan cover)		RAL 7030				
	Terminal Box Position		Top - A1				
	Cable entries		2 x M40x1,5 + 1 x M16x1,5				
	Direction of rotation		← / →				
	Drain hole(s)		Lowest point - with plug				
	Bearing DE		6311 ZZ C3				
	Bearing NDE		6311 ZZ C3				
	Shaft dimensions	mm	48 x 110				
	Oilseals DE / NDE	mm	55 x 75 x 5,5		55 x 75 x 5,5		
	Balancing (Class)		Half Key		A (IEC 60034-14)		
	Sound level - L(p)A	dB(A)	65,0	50Hz - at 1m - no load			
	Weight	Kg	227,0				
	Options & Extras		PTC				
	HS Code		85015230 90				

Every care has been taken to ensure the accuracy of the information contained in this document. Due to our policy of continuous development and improvement, Electramo reserves the right to supply products which may differ from those illustrated and described in this document. Descriptions and technical features listed in this document may not be considered as binding. Under no circumstances should data in this document be considered as a contractual obligation.