



MLFB-Ordering data: **1LE1501-2AA43-4AA4**

Motor type: **1CV2204A**

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U [V]	Δ/Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			I _A /I _N I/I _N	M _A /M _N T _f /T _N	M _k /M _N T _B /T _N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
400	Δ	50	30.00	- / -	54.00	2960	97.0	92.0	92.3	91.8	0.87	0.83	0.75	6.9	2.5	3.3	IE2
690	Y	50	30.00	- / -	31.50	2960	97.0	92.0	92.3	91.8	0.87	0.83	0.75	6.9	2.5	3.3	IE2
460	Δ	60	33.50	- / -	53.00	3560	90.0	92.4	92.4	91.5	0.87	0.84	0.76	6.9	2.5	3.3	IE2
460	Δ	60	30.00	- / -	47.50	3565	80.0	91.7	91.5	90.3	0.86	0.82	0.73	7.7	2.9	3.8	IE2
IM B3 / IM 1001		FS 200 L		200 kg	IP55	CC032A	IEC/EN 60034		IEC, DIN, ISO, VDE, EN								

Mechanical data			Terminal box	
Sound pressure level 50Hz/60Hz (load)	78 dB(A)	81 dB(A)	Terminal box position	top
Moment of inertia	0.13 kg m ²		Material of terminal box	cast iron
Bearing DE NDE	6212 Z C3	6212 Z C3	Type of terminal box	TB1 L01
Bearing lifetime	40000 h		Contact screw thread	M6
Lubricants	Esso Unirex N3		Max. cross-sectional area	25.0 mm ²
Regreasing device	No		Cable diameter from ... to ...	27.0 mm - 35.0 mm
Grease nipple	- / -		Cable entry	2xM50x1,5
Type of bearing	Locating bearing NDE		Cable gland	2 plugs
Condensate drainage holes	Yes (standard)		Special design (0)	
External earthing terminal	Yes (standard)			
Vibration severity grade	A			
Insulation	155(F) to 130(B)			
Duty type	S1			
Direction of rotation	bidirectional			
Frame material	cast iron			
Data of anti condensation heating	- / -			
Coating (paint finish)	Standard paint finish C2			
Color, paint shade	RAL7030			
Motor protection	(A) without (Standard)			
Method of cooling	IC411 - self ventilated, surface cooled			

Environmental conditions	
Ambient temperature	-20 °C - +40 °C
Altitude above sea level	1000 m