



MLFB-Ordering data: **1LE1003-1DA23-4AB4**

Motor type: **1AV3162A**

Client order no.:

Item no.:

Order no.:

Consignment no.:

Offer no.:

Project:

Remarks:

U [V]	Δ/Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	NOM. EFF at ... load [%]			Power factor at ... load			I <sub>A</sub> /I <sub>N</sub> I/I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub> T <sub>f</sub> /T <sub>N</sub>	M <sub>k</sub> /M <sub>N</sub> T <sub>B</sub> /T <sub>N</sub>	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
400	Δ	50	11.00	- / -	19.60	2955	36.0	91.2	91.0	89.5	0.89	0.86	0.78	7.9	2.4	3.8	IE3
690	Y	50	11.00	- / -	11.40	2955	36.0	91.2	91.0	89.5	0.89	0.86	0.78	7.9	2.4	3.8	IE3
460	Δ	60	12.60	- / -	19.50	3555	33.0	91.0	90.7	89.0	0.89	0.87	0.80	7.9	2.8	3.7	IE3
460	Δ	60	11.00	- / -	17.20	3560	30.0	91.0	90.2	88.0	0.88	0.85	0.77	8.9	3.2	4.3	IE3
IM B3 / IM 1001		FS 160 M		75 kg	IP55	CC032A	IEC/EN 60034		IEC, DIN, ISO, VDE, EN								

Mechanical data			Terminal box	
Sound pressure level 50Hz/60Hz (load)	70 dB(A)	77 dB(A)	Terminal box position	top
Moment of inertia	0.053 kg m <sup>2</sup>		Material of terminal box	Aluminium
Bearing DE   NDE	6209 2Z C3	6209 2Z C3	Type of terminal box	TB1 J00
Bearing lifetime	40000 h		Contact screw thread	M5
Lubricants	Esso Unirex N3		Max. cross-sectional area	16.0 mm <sup>2</sup>
Regreasing device	No		Cable diameter from ... to ...	19.0 mm - 28.0 mm
Grease nipple	- / -		Cable entry	2xM40x1,5-1xM16x1,5
Type of bearing	Locating bearing NDE		Cable gland	3 plugs
Condensate drainage holes	No		Special design (0)	
External earthing terminal	No			
Vibration class	A			
Insulation	155(F) to 130(B)			
Duty type	S1			
Direction of rotation	bidirectional			
Frame material	aluminum			
Data of anti condensation heating	-/-			
Coating (paint finish)	Standard paint finish C2			
Color, paint shade	RAL7030			
Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)			
Method of cooling	IC411 - self ventilated, surface cooled			

Environmental conditions	
Ambient temperature	-20 °C - +40 °C
Altitude above sea level	1000 m