

Data Sheet

Electramo NV Industrieweg 14 B-2390 Malle Belgium +32 3 311 65 40 info@electramo.com www.electramo.com BE 0414.941.452	Electric motor Type Efficiencies Insulation class Temperatures Connection - Phases Tension V Frequency Hz Output kW Speed min⁻¹ Current A Efficiency % Cos φ Starting Current A No Load Current A Nominal Torque Nm Starting Torque Nm Maximum Torque Nm Construction Mounting position Protection Cooling method Duty type Tropical treatment Max. altitude A.S.L. Paint (body / fan cover) Terminal Box Position Cable entries Direction of rotation Drain hole(s) Bearing DE Bearing NDE Shaft dimensions mm Oilseals DE / NDE mm Balancing (Class) Sound level - L(p)A dB(A) Weight Kg Options & Extras	HMS100L1-2 - 3kW - 2890 rpm - 400V/690V - 50Hz IEC60034-30 IE3 F / B -20°C / +40°C <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 10%;"></th> <th style="width: 15%; text-align: center;">Δ</th> <th style="width: 15%; text-align: center;">Y</th> <th style="width: 15%; text-align: center;">Δ</th> <th style="width: 15%; text-align: center;">Δ</th> <th style="width: 15%; text-align: center;">Δ</th> </tr> </thead> <tbody> <tr> <td></td> <td style="text-align: center;">400</td> <td style="text-align: center;">690</td> <td style="text-align: center;">440</td> <td style="text-align: center;">460</td> <td style="text-align: center;">480</td> </tr> <tr> <td></td> <td style="text-align: center;">50</td> <td style="text-align: center;">50</td> <td style="text-align: center;">60</td> <td style="text-align: center;">60</td> <td style="text-align: center;">60</td> </tr> <tr> <td></td> <td style="text-align: center;">3,00</td> <td style="text-align: center;">3,00</td> <td style="text-align: center;">3,60</td> <td style="text-align: center;">3,60</td> <td style="text-align: center;">3,60</td> </tr> <tr> <td></td> <td style="text-align: center;">2.890</td> <td style="text-align: center;">2890</td> <td style="text-align: center;">3470</td> <td style="text-align: center;">3470</td> <td style="text-align: center;">3470</td> </tr> <tr> <td></td> <td style="text-align: center;">5,60</td> <td style="text-align: center;">3,20</td> <td style="text-align: center;">6,10</td> <td style="text-align: center;">5,82</td> <td style="text-align: center;">5,60</td> </tr> <tr> <td></td> <td style="text-align: center;">100%</td> <td style="text-align: center;">75%</td> <td style="text-align: center;">50%</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">87,10</td> <td style="text-align: center;">87,50</td> <td style="text-align: center;">86,80</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">100%</td> <td style="text-align: center;">75%</td> <td style="text-align: center;">50%</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">0,89</td> <td style="text-align: center;">0,84</td> <td style="text-align: center;">0,75</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">8,90</td> <td style="text-align: center;">Ia/In</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">2,19</td> <td style="text-align: center;">400V 50Hz</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">9,83</td> <td style="text-align: center;">Nm</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">3,27</td> <td style="text-align: center;">Ms/Mn</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">3,26</td> <td style="text-align: center;">Mmax/Mn</td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td colspan="5">Aluminum</td> </tr> <tr> <td></td> <td colspan="5">B3 - IM1001 - feet - horizontal</td> </tr> <tr> <td></td> <td colspan="5">IP 55</td> </tr> <tr> <td></td> <td colspan="5">IC411</td> </tr> <tr> <td></td> <td colspan="5">S1</td> </tr> <tr> <td></td> <td colspan="5">95%</td> </tr> <tr> <td></td> <td colspan="5">1000 m</td> </tr> <tr> <td></td> <td colspan="5">RAL 7030 - RAL 9005</td> </tr> <tr> <td></td> <td colspan="5">Top - A1</td> </tr> <tr> <td></td> <td colspan="5">2 x M20x1,5 + 1 x M16x1,5</td> </tr> <tr> <td></td> <td colspan="5">← / →</td> </tr> <tr> <td></td> <td colspan="5">Lowest point - with plug</td> </tr> <tr> <td></td> <td colspan="5">6206 2RS C3</td> </tr> <tr> <td></td> <td colspan="5">6206 2RS C3</td> </tr> <tr> <td></td> <td style="text-align: center;">28 x 60</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">30 x 42 x 7</td> <td></td> <td style="text-align: center;">30 x 42 x 7</td> <td></td> <td></td> </tr> <tr> <td></td> <td colspan="2">Half Key</td> <td colspan="3">A (IEC 60034-14)</td> </tr> <tr> <td></td> <td style="text-align: center;">76,0</td> <td colspan="4" style="text-align: center;">50Hz - at 1m - no load</td> </tr> <tr> <td></td> <td colspan="5">25,9</td> </tr> <tr> <td></td> <td colspan="5">PTC</td> </tr> <tr> <td>HS Code</td> <td colspan="5">85015220 89</td> </tr> </tbody> </table>		Δ	Y	Δ	Δ	Δ		400	690	440	460	480		50	50	60	60	60		3,00	3,00	3,60	3,60	3,60		2.890	2890	3470	3470	3470		5,60	3,20	6,10	5,82	5,60		100%	75%	50%				87,10	87,50	86,80				100%	75%	50%				0,89	0,84	0,75				8,90	Ia/In					2,19	400V 50Hz					9,83	Nm					3,27	Ms/Mn					3,26	Mmax/Mn					Aluminum						B3 - IM1001 - feet - horizontal						IP 55						IC411						S1						95%						1000 m						RAL 7030 - RAL 9005						Top - A1						2 x M20x1,5 + 1 x M16x1,5						← / →						Lowest point - with plug						6206 2RS C3						6206 2RS C3						28 x 60						30 x 42 x 7		30 x 42 x 7				Half Key		A (IEC 60034-14)				76,0	50Hz - at 1m - no load					25,9						PTC					HS Code	85015220 89				
	Δ	Y	Δ	Δ	Δ																																																																																																																																																																																																																					
	400	690	440	460	480																																																																																																																																																																																																																					
	50	50	60	60	60																																																																																																																																																																																																																					
	3,00	3,00	3,60	3,60	3,60																																																																																																																																																																																																																					
	2.890	2890	3470	3470	3470																																																																																																																																																																																																																					
	5,60	3,20	6,10	5,82	5,60																																																																																																																																																																																																																					
	100%	75%	50%																																																																																																																																																																																																																							
	87,10	87,50	86,80																																																																																																																																																																																																																							
	100%	75%	50%																																																																																																																																																																																																																							
	0,89	0,84	0,75																																																																																																																																																																																																																							
	8,90	Ia/In																																																																																																																																																																																																																								
	2,19	400V 50Hz																																																																																																																																																																																																																								
	9,83	Nm																																																																																																																																																																																																																								
	3,27	Ms/Mn																																																																																																																																																																																																																								
	3,26	Mmax/Mn																																																																																																																																																																																																																								
	Aluminum																																																																																																																																																																																																																									
	B3 - IM1001 - feet - horizontal																																																																																																																																																																																																																									
	IP 55																																																																																																																																																																																																																									
	IC411																																																																																																																																																																																																																									
	S1																																																																																																																																																																																																																									
	95%																																																																																																																																																																																																																									
	1000 m																																																																																																																																																																																																																									
	RAL 7030 - RAL 9005																																																																																																																																																																																																																									
	Top - A1																																																																																																																																																																																																																									
	2 x M20x1,5 + 1 x M16x1,5																																																																																																																																																																																																																									
	← / →																																																																																																																																																																																																																									
	Lowest point - with plug																																																																																																																																																																																																																									
	6206 2RS C3																																																																																																																																																																																																																									
	6206 2RS C3																																																																																																																																																																																																																									
	28 x 60																																																																																																																																																																																																																									
	30 x 42 x 7		30 x 42 x 7																																																																																																																																																																																																																							
	Half Key		A (IEC 60034-14)																																																																																																																																																																																																																							
	76,0	50Hz - at 1m - no load																																																																																																																																																																																																																								
	25,9																																																																																																																																																																																																																									
	PTC																																																																																																																																																																																																																									
HS Code	85015220 89																																																																																																																																																																																																																									

Every care has been taken to ensure the accuracy of the information contained in this document. Due to our policy of continuous development and improvement, Electramo reserves the right to supply products which may differ from those illustrated and described in this document. Descriptions and technical features listed in this document may not be considered as binding. Under no circumstances should data in this document be considered as a contractual obligation.